



OC HILIGHT™ UNMATCHED CLARITY FOR TRANSLUCENT PANELS

OC HiLight™ multi-end roving represents a compelling solution for panels where excellent translucency performance is required.

- Produced with patented Advantex® corrosion resistant E-CR glass by Owens Corning.
- Compatible with unsaturated polyester resins.
- Based on process and resin system, OC HiLight™ roving can be used as an alternative to OC Paneluxe™ roving.

Product Benefits

Excellent Processability

- Designed for excellent processing at various line speeds, OC HiLight™ roving features easy unwinding and chopping, flat lay-down, and uniform dispersion with low fuzz and static.
- With high impregnation and wet-through characteristics, the product allows excellent resin flow in translucent applications.

Impressive Aesthetics

- Excellent fiber distribution provides a homogeneous surface aspect with limited fiber prints, resulting in consistent thickness throughout the laminate.
- Absence of white fibers and fiber spring-back along with significant reduction of air entrapment ensures excellent translucency of laminates.

Enhanced Service Life

- Advantex® glass helps fight corrosion, enhancing service life compared to standard E-glass.

Application

OC HiLight™ roving is designed to provide optimal translucency in skylight panels, greenhouses, decorative panels for commercial buildings, and roofs for trucks and industrial buildings.



Technical Characteristics (Nominal Values)

LINEAR WEIGHT OF ROVING (TEX)	YIELDS (YDS/LB)	LOSS ON IGNITION (%) ISO 1887:1995
2400	207	0.65
4800	103	0.65

Availability & Packaging

Each pallet can be packaged in bulk or Creel-Pak™ packaging format. Pallets are stretch-wrapped for load stability and for protection during transport. All individual packages are wrapped with Tack-Pak™ packaging to aid package run-out and transfer. More information is available in the Customer Acceptance Standards.

MANUFACTURING REGION	PRODUCT	LAYERS PER PALLET	DOFFS PER LAYER	NUMBER OF ENDS	PALLET NET WEIGHT (KG/LB)
North America	OC HiLight® 2400/4800 tex	3	16	16	820/1,808

Labeling

Each doff has a self-adhesive identification label showing the product description, net weight and production date. Each pallet has at least two identification labels detailing the product reference, pallet net and gross weights, production date and pallet production code.

Storage

It is recommended to store glass fiber products in a cool, dry area. The glass fiber products must remain in their original packaging material until the point of usage; the product should be stored in the workshop, within its original packaging, 48 hours prior to its utilization, to allow it to reach the workshop temperature condition and prevent condensation, especially during cold season. The packaging is not waterproof. Be sure to protect the product from the weather and other sources of water. When stored properly, there is no known shelf life to the product, but retesting is advised after two years from the initial production date to insure optimum performance.



Americas

Owens Corning Composite Materials, LLC.

One Owens Corning Parkway
Toledo, Ohio, USA 43659
1-800-GET-PINK®

<https://www.owenscorning.com/composites> | Composites@owenscorning.com

This information and data contained herein is offered solely as a guide in the selection of product. We believe this information to be reliable, but do not guarantee its applicability to the user's process or assume any responsibility or liability arising out of its use or performance. The user agrees to be responsible for thoroughly testing any application of the product to determine its suitability. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose. Statements in this publication shall not be construed as representations or warranties or as inducements to infringe any patent or violate any law, safety code or insurance regulation. We reserve the right to modify this document without prior notice.

Picture courtesy of Rivasca, IT.

Pub no. 10013904-A. OC HiLight_MER_product data sheet_na_10-2019_Rev2. March 2020. English.

THE PINK PANTHER™ & © 1964–2020 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. © 2020 Owens Corning. All Rights Reserved.